

JIS-G	O型圈的尺寸 (单位 : mm)		
公称编号	线径 C/S	内径 d	
G 3	3.1	±0.10	2.4 ±0.14
G 4			3.4 ±0.14
G 5			4.4 ±0.15
G 6			5.4 ±0.15
G 7			6.4 ±0.16
G 8			7.4 ±0.16
G 9			8.4 ±0.17
G 10			9.4 ±0.17
G 11			10.4 ±0.18
G 12			11.4 ±0.18
G 13			12.4 ±0.19
G 14			13.4 ±0.19
G 15			14.4 ±0.20
G 16			15.4 ±0.20
G 17			16.4 ±0.21
G 18			17.4 ±0.21
G 19			18.4 ±0.22
G 20			19.4 ±0.22
G 21			20.4 ±0.23
G 22			21.4 ±0.24
G 23			22.4 ±0.24
G 24			23.4 ±0.24
G 25			24.4 ±0.25
G 30			29.4 ±0.29
G 35			34.4 ±0.33
G 40			39.4 ±0.37
G 45			44.4 ±0.41
G 50			49.4 ±0.45
*G 52	51.4 ±0.47		
G 55	54.4 ±0.49		
*G 58	57.4 ±0.51		
G 60	59.4 ±0.53		
*G 62	61.4 ±0.54		
*G 63	62.4 ±0.55		
*G 64	63.4 ±0.56		
G 65	64.4 ±0.57		

JIS-G	O型圈的尺寸 (单位 : mm)		
公称编号	线径 C/S	内径 d	
*G 67	3.1	±0.10	66.4 ±0.59
G 70			69.4 ±0.61
*G 72			71.4 ±0.63
G 75			74.4 ±0.65
G 80			79.4 ±0.69
G 85			84.4 ±0.73
G 90			89.4 ±0.77
G 95			94.4 ±0.81
G 100			99.4 ±0.85
G 105			104.4 ±0.87
G 110			109.4 ±0.91
G 115			114.4 ±0.94
G 120			119.4 ±0.98
G 125			124.4 ±1.01
G 130			129.4 ±1.05
G 135			134.4 ±1.08
G 140			139.4 ±1.12
G 145			144.4 ±1.16
*GS 150			149.3 ±1.19
*GS 155			154.3 ±1.23
*GS 160			159.3 ±1.26
*GS 165			164.3 ±1.30
*GS 170			169.3 ±1.33
*GS 175			174.3 ±1.37
*GS 180			179.3 ±1.40
*GS 185			184.3 ±1.44
*GS 190			189.3 ±1.47
*GS 195			194.3 ±1.51
*GS 200	199.3 ±1.55		
*GS 205	204.3 ±1.58		
*GS 210	209.3 ±1.61		
*GS 215	214.3 ±1.65		
*GS 220	219.3 ±1.68		
*GS 225	224.3 ±1.71		
*GS 230	229.3 ±1.75		
*GS 235	234.3 ±1.78		

JIS-G	O型圈的尺寸 (单位 : mm)		
公称编号	线径 C/S	内径 d	
*GS 240	±0.10	3.1	239.3 ±1.81
*GS 245			244.3 ±1.85
*GS 250			249.3 ±1.88
*GS 255			254.3 ±1.91
*GS 260			259.3 ±1.94
*GS 265			264.3 ±1.98
*GS 270			269.3 ±2.01
*GS 275			274.3 ±2.04
*GS 280			279.3 ±2.07
*GS 285			284.3 ±2.11
*GS 290			289.3 ±2.14
*GS 295			294.3 ±2.17
*GS 300			299.3 ±2.20
*GS 305			304.3 ±2.24
*GS 310	309.3 ±2.27		
*GS 315	314.3 ±2.30		
*GS 320	319.3 ±2.33		
*GS 325	324.3 ±2.36		
*GS 330	329.3 ±2.39		
*GS 335	334.3 ±2.42		
*GS 340	339.3 ±2.45		
*GS 345	344.3 ±2.48		
*GS 350	349.3 ±2.51		
*GS 355	354.3 ±2.54		
*GS 360	359.3 ±2.57		
*GS 365	364.3 ±2.60		
*GS 370	369.3 ±2.63		
*GS 375	374.3 ±2.67		
*GS 380	379.3 ±2.70		
*GS 385	384.3 ±2.73		
*GS 390	389.3 ±2.77		
*GS 395	394.3 ±2.79		
*GS 400	399.3 ±2.82		
*GS 405	404.3		
*GS 410	409.3 ±3.00		
*GS 415	414.3		

JIS-G	O型圈的尺寸 (单位 : mm)		
公称编号	线径 C/S	内径 d	
*GS 420	3.1	±0.12	419.3 ±3.00
*GS 425			424.3
*GS 430			429.3
*GS 435			434.3
*GS 440			439.3
*GS 445			444.3
*GS 450			449.3
*GS 455			454.3
*GS 460			459.3
*GS 465			464.3
*GS 470			469.3
*GS 475			474.3
*GS 480			479.3 ±3.30
*GS 485			484.3
*GS 490	489.3		
*GS 495	494.3		
*GS 500	499.3		
G 150	5.7	±0.13	149.3 ±1.19
G 155			154.3 ±1.23
G 160			159.3 ±1.26
G 165			164.3 ±1.30
G 170			169.3 ±1.33
G 175			174.3 ±1.37
G 180			179.3 ±1.40
G 185			184.3 ±1.44
G 190			189.3 ±1.47
G 195			194.3 ±1.51
G 200			199.3 ±1.55
*G 205			204.3 ±1.58
G 210			209.3 ±1.61
*G 215			214.3 ±1.65
G 220	219.3 ±1.68		
*G 225	224.3 ±1.71		
G 230	229.3 ±1.73		
*G 235	234.3 ±1.78		

# : 其他尺寸亦可提供 ! (单位 : 毫米/mm)

JIS-G	O型圈的尺寸 (单位 : mm)		
公称编号	线径 C/S	内径 d	
G 240	5.7	±0.13	239.3 ±1.81
*G 245			244.3 ±1.84
G 250			249.3 ±1.88
*G 255			254.3 ±1.91
G 260			259.3 ±1.94
*G 265			264.3 ±1.97
G 270			269.3 ±2.01
*G 275			274.3 ±2.04
G 280			279.3 ±2.07
*G 285			284.3 ±2.10
G 290			289.3 ±2.14
*G 295			294.3 ±2.17
G 300			299.3 ±2.20
*G 305			304.3 ±2.24
*G 310			309.3 ±2.27
*G 315			314.3 ±2.30
*G 320			319.3 ±2.33
*G 325			324.3 ±2.36
*G 330			329.3 ±2.39
*G 335			334.3 ±2.42
*G 340			339.3 ±2.45
*G 345			344.3 ±2.48
*G 350			349.3 ±2.51
*G 355			354.3 ±2.54
*G 360			359.3 ±2.57
*G 365			364.3 ±2.60
*G 370			369.3 ±2.63
*G 375			374.3 ±2.67
*G 380			379.3 ±2.70
*G 385			384.3 ±2.73
*G 390			389.3 ±2.77
*G 395			394.3 ±2.79
*G 400			399.3 ±2.82
*G 405			404.3 ±3.00
*G 410			409.3
*G 415			414.3

JIS-G	O型圈的尺寸 (单位 : mm)		
公称编号	线径 C/S	内径 d	
*G 420	5.7	±0.15	419.3 ±3.00
*G 425			424.3
*G 430			429.3
*G 435			434.3
*G 440			439.3
*G 445			444.3
*G 450			449.3
*G 455			454.3
*G 460			459.3
*G 465			464.3
*G 470			469.3
*G 475			474.3
*G 480			479.3 ±3.30
*G 485			484.3
*G 490			489.3
*G 495			494.3
*G 500			499.3
*G 505			504.3
*G 510			509.3
*G 515			514.3
*G 520			519.3
*G 525			524.3 ±3.70
*G 530			529.3
*G 535			534.3
*G 540			539.3
*G 545			544.3
*G 550			549.3
*G 555			554.3
*G 560			559.3
*G 565			564.3
*G 570			569.3
*G 575	574.3 ±4.00		
*G 580	579.3		
*G 585	584.3		
*G 590	589.3		
*G 595	594.3		

JIS-G	O型圈的尺寸 (单位 : mm)		
公称编号	线径 C/S	内径 d	
*G 600	5.7	±0.15	599.3 ±4.00
*G 610			609.3
*G 620			619.3
*G 630			629.3
*G 640			639.3
*G 650			649.3
*G 660			659.3
*G 670			669.3
*G 680			679.3 ±4.70
*G 690			689.3
*G 700			699.3
*G 710			709.3
*G 720			719.3
*G 730			729.3
*G 740			739.3
*G 750			749.3
*G 760			759.3
*G 770			769.3
*G 780			779.3 ±5.30
*G 790			789.3
*G 800			799.3
*G 810			809.3
*G 820			819.3
*G 830			829.3
*G 840			839.3
*G 850			849.3
*G 860			859.3 ±6.00
*G 870			869.3
*G 880			879.3
*G 890			889.3
*G 900			899.3
*G 910	909.3		
*G 920	919.3		
*G 930	929.3 ±6.70		
*G 940	939.3		
*G 950	949.3		

JIS-G	O型圈的尺寸 (单位 : mm)		
公称编号	线径 C/S	内径 d	
*G 960	5.7	±0.15	959.3
*G 970			969.3
*G 980			979.3 ±6.70
*G 990			989.3
*G 1000			999.3
*G 1020			1019.3
*G 1040			1039.3
*G 1060			1059.3
*G 1080			1079.3
*G 1100			1099.3
*G 1120			1119.3
*G 1140			1139.3
*G 1160			1159.3
*G 1180			1179.3
*G 1200			1199.3
*G 1220	1219.3		
*G 1240	1239.3		
*G 1260	1259.3 ±7.50		
*G 1280	1279.3		
*G 1300	1299.3		
*G 1320	1319.3		
*G 1340	1339.3		
*G 1360	1359.3		
*G 1380	1379.3		
*G 1400	1399.3		
*G 1420	1419.3		
*G 1440	1439.3		
*G 1460	1459.3		
*G 1480	1479.3		
*G 1500	1499.3		

# : 其他尺寸亦可提供 ! ( 单位 : 毫米/mm )